

**AMENDMENTS TO THE CLAIMS**

1. (Canceled)

2. (Canceled)

3. (Canceled)

4. (Canceled)

5. (Canceled)

6. (Canceled)

7. (Canceled)

8. (Previously presented) A backlight unit for illuminating an object to be illuminated using a plurality of light sources disposed directly below the object to be illuminated, wherein the backlight unit has a reflection portion for causing the light from the plurality of light sources to exit toward a certain direction, wherein the reflection portion comprises at least a first and a second reflection layers having a predetermined level of light reflectance and transmittance, wherein the reflection portion consists of a first region with the first and second reflection layers being overlapped in the incident direction of light located at a position equivalent to the central

portion on the surface to be illuminated of the object to be illuminated and a second region consisting of the first reflection layer only, and wherein brightness gradient is formed in the horizontal and vertical directions on the surface to be illuminated of the object to be illuminated by controlling reflectance of the reflection portion using the first region with relatively higher reflectance and the second region with lower reflectance than the first region.

9. (Previously presented) A backlight unit for illuminating an object to be illuminated using a plurality of light sources disposed directly below the object to be illuminated, wherein the backlight unit has a reflection portion for causing the light from the plurality of light sources to exit toward a certain direction, wherein the reflection portion comprises at least a first and a second reflection layers having a predetermined level of light reflectance and transmittance, wherein the reflection portion consists of a first region with the first and second reflection layers being overlapped in the incident direction of light located at a position equivalent to the central portion in the horizontal direction on the surface to be illuminated of the object to be illuminated, and a second region consisting of the first reflection layer only located at the both ends, and wherein brightness gradient is formed in the horizontal and vertical directions on the surface to be illuminated of the object to be illuminated by controlling reflectance of the reflection portion in the horizontal direction on the surface to be illuminated and also by making the brightness of the light sources located at the position equivalent to the central portion in the vertical direction on the surface to be illuminated relatively higher than the brightness of the light sources located at the both ends, using the first region with relatively higher reflectance and the second region with lower reflectance than the first region.

10. (Previously presented) A backlight unit for illuminating an object to be illuminated using a plurality of light sources disposed directly below the object to be illuminated, wherein the backlight unit has a reflection portion for causing the light from the plurality of light sources to exit toward a certain direction, wherein the reflection portion comprises at least a first and a second reflection layers having a predetermined level of light reflectance and transmittance, wherein the reflection portion consists of a first region with the first and second reflection layers overlapped in the incident direction of light located at a position equivalent to the central portion in the vertical direction on the surface to be illuminated of the object to be illuminated and a second region consisting of the first reflection layer only located at the both ends, and wherein brightness gradient is formed in the horizontal and vertical directions on the surface to be illuminated of the object to be illuminated by controlling reflectance of the reflection portion in the vertical direction on the surface to be illuminated and also by making the brightness of the light sources located at the position equivalent to the central portion in the horizontal direction on the surface to be illuminated relatively higher than the brightness of the light sources located at the both ends, using the first region with relatively higher reflectance and the second region with lower reflectance than the first region.

11. (Canceled)

12. (Canceled)

13. (Canceled)

14. (Canceled)

15. (Canceled)

16. (Canceled)

17. (Canceled)

18. (Canceled)

19. (Canceled)

20. (Previously presented) A backlight unit for illuminating an object to be illuminated using a plurality of light sources disposed directly below the object to be illuminated, wherein the plurality of light sources comprise LEDs, wherein brightness gradient is formed in the horizontal and vertical directions on the surface to be illuminated of the object to be illuminated by controlling radiation brightness of the LEDs in each of the regions formed on the substrate of the backlight unit.

21. (Previously presented) The backlight unit of claim 20, wherein the radiation brightness of the LEDs differs from each other in regions which are concentrically formed around the center of the substrate of the backlight unit.

22. (Canceled)

23. (Canceled)

24. (Currently amended) A liquid crystal display device comprising the backlight unit of claim 20 or 21 and a liquid crystal panel to be illuminated by the backlight unit.

25. (Canceled)

26. (Canceled)

27. (Canceled)

28. (Canceled)

29. (Original) A backlight unit for illuminating an object to be illuminated using a plurality of light sources disposed directly below the object to be illuminated, wherein the backlight unit has a reflection portion for causing the light from the plurality of light sources to exit toward a

certain direction, wherein the reflection portion comprises at least a first and a second reflection layers having a predetermined level of light reflectance and transmittance, wherein the reflection portion consists of a first region with the first and second reflection layers being overlapped in the incident direction of light located at a position equivalent to the central portion in the horizontal direction on the surface to be illuminated of the object to be illuminated, and a second region consisting of the first reflection layer only located at the both ends, and wherein brightness gradient is formed in the horizontal and vertical directions on the surface to be illuminated of the object to be illuminated by controlling reflectance of the reflection portion in the horizontal direction on the surface to be illuminated and also by making the clearance of the light sources located at the position equivalent to the central portion in the vertical direction on the surface to be illuminated relatively smaller than the clearance of the light sources located at the both ends, using the first region with relatively higher reflectance and the second region with lower reflectance than the first region.

30. (Original) A backlight unit for illuminating an object to be illuminated using a plurality of light sources disposed directly below the object to be illuminated, wherein the backlight unit has a reflection portion for causing the light from the plurality of light sources to exit toward a certain direction, wherein the reflection portion comprises at least a first and a second reflection layers having a predetermined level of light reflectance and transmittance, wherein the reflection portion consists of a first region with the first and second reflection layers overlapped in the incident direction of light located at a position equivalent to the central portion in the vertical direction on the surface to be illuminated of the object to be illuminated and a second region

consisting of the first reflection layer only located at the both ends, and wherein brightness gradient is formed in the horizontal and vertical directions on the surface to be illuminated of the object to be illuminated by controlling reflectance of the reflection portion in the vertical direction on the surface to be illuminated and also by making the clearance of the light sources located at the position equivalent to the central portion in the horizontal direction on the surface to be illuminated relatively smaller than the clearance of the light sources located at the both ends, using the first region with relatively higher reflectance and the second region with lower reflectance than the first region.

31. (Currently amended) A liquid crystal display device comprising the backlight unit of ~~any of claims 8 to 10, 29 and 30~~ claim 8 and a liquid crystal panel to be illuminated by the backlight unit.

32. (New) A liquid crystal display device comprising the backlight unit of claim 21 and a liquid crystal panel to be illuminated by the backlight unit.

33. (New) A liquid crystal display device comprising the backlight unit of claim 9 and a liquid crystal panel to be illuminated by the backlight unit.

34. (New) A liquid crystal display device comprising the backlight unit of claim 10 and a liquid crystal panel to be illuminated by the backlight unit.

35. (New) A liquid crystal display device comprising the backlight unit of claim 29 and a liquid crystal panel to be illuminated by the backlight unit.

36. (New) A liquid crystal display device comprising the backlight unit of claim 30 and a liquid crystal panel to be illuminated by the backlight unit.